# B572 Surface attached adjuster cross hole type PAT.P

#### Adjuster cap











B572-25-WH

B572-25-BL

wooden part • Size is  $\phi$  25

places Installation is easy. Even if it needs an adjuster, it's possible to install with only a driver.

• Having cross hole makes it possible to use a driver at

• Impositioning makes it unnecessary to process into

It's possible to install on verious kinds of

even small place not turning by finger

- Superial material being durable for low temperature, so
- it's not broken easily
- Adjustment width 5mm
- Recommended screw/round screw for wood  $\phi$  3.5, Pan head screw  $\phi$  3.5
- Indoor use
- Finishing/ White Black
- Material/POM

\*Load capacity is static load Caution: It might happen to be broken if it gets shock within its load capacity

 Please refrain to use things such as a chair or sofa expecting shock When you use, use in a tightened state


Specification dimension Product number Specification Load capacity (kg) Quantity White B572-25-BL Black 240 B572-25-PL WH/BL(seat) WH/BL(cap) B572-25-CP

If the movement of adjustment is hard, tighten a screw of adjustment seat so that it does not wobble.

Caution: Using an impact driver, if you screw too tightened, movement of adjustment might become hard.

### New adjuster with cross hole!!





Installation image









B572-25-BL


Installation image (Only adjust seat)




B572-25-WH / BL









Recommended screw/round wood screw  $\phi$ 3.5, pan head screw  $\phi$ 3.5

METAL FITTING CORPORATION



3-4-1 Motoasakusa, Taito-ku, Tokyo 111-0041, Japan TEL +81-3-3843-3141 FAX +81-3-3843-3144

Kasukabe branch 1-26-20 Kasukabehigashi, Kasukabe-shi, Saitama 344-0062, Japan TEL +81-48-760-3881 FAX +81-48-760-3883





# B573 Surface attached adjuster felf type PAT.P

#### Adjuster cap







B573-25-BL

#### Adjuster seat





- Hard to scratch contact area because of felt
- Imposition makes unnecessary to process into wooden part
- Size is  $\phi$  25. It's possible to install thin and small surface such table legs
- Installation is easy. Even if it needs an adjuster, it's possible to install with only a driver.
- Superial material being durable for low temperature, so it's not broken easily
- Easy to turn because it has knurling
- Adjustment width is 5mm
- Recommended screw/round screw for wood  $\phi$  3.5, Panhead screw  $\phi$  3.5
- Indoor use
- Finishing/ White · Black
- Material/POM
- Applicable floor material/P tile, flooring
- \*\*Load capacity is static load Caution: It might happen to be broken if it gets shock within its load capacity
- Please refrain to use things such as a chair or sofa expecting shock When you use, use in a tightened state a cap

# Save time to work!! Usual item (current) Necessary to process of wood Fix with screw directly

# Specification dimension Unit : mm Product number Specification Load capacity(kg) Quantity B573-25-WH White 150 40 <

If the movement of adjustment is hard, tighten a screw of adjustment seat so that it does not wobble.

Caution: Using an impact driver, if you screw too tightened, movement of adjustment might become hard.

#### **Installation image**




B573-25-WH





B573-25-BL

# Installation image (Only adjust seat)









M20 P=1.5

Recommended screw/round screw for wood  $\phi$ 3.5, pan head screw  $\phi$ 3.5

\*\*Real total height becomes 17mm with felt



Head office

3-4-1 Motoasakusa, Taito-ku, Tokyo 111-0041, Japan TEL +81-3-3843-3141 FAX +81-3-3843-3144

Kasukabe branch 1-26-20 Kasukabehigashi, Kasukabe-shi, Saitama 344-0062, Japan TEL +81-48-760-3881 FAX +81-48-760-3883



