B572 Surface attached adjuster cross hole type PAT.P

Adjuster cap










B572-25-WH

B572-25-BL

·



places

• Installation is easy. Even if it needs an adjuster, it's possible to install with only a driver.

• Superial material being durable for low temperature, so it's not broken easily

Adjustment width 5mm

- Recommended screw/round screw for wood ϕ 3.5, Panhead screw ϕ 3.5
- Indoor use
- Finishing/ White Black
- Material/POM

**Load capacity is static load Caution: It might happen to be broken if it gets shock within its load capacity


 Please refrain to use things such as a chair or sofa expecting shock When you use, use in a tightened state a cap


Specification dimension Unit : mm Product number Specification Load capacity(kg) Quantity B572-25-WH White 150 B572-25-BL Black B572-25-PL WH / BL (seat) B572-25-CP WH / BL (cap)


If the movement of adjustment is hard, tighten a screw of adjustment seat so that it does not wobble.

Caution: Using an impact driver, if you screw too tightened, movement of adjustment might become hard.

New adjuster with cross hole!!







Installation image





B572-25-BL


Installation image (Only adjust seat)




B572-25-WH / BL









Recommended screw/round wood screw ϕ 3.5, pan head screw ϕ 3.5

KOJIMA METAL FITTING CORPORATION

Head office

3-4-1 Motoasakusa, Taito-ku, Tokyo 111-0041, Japan TEL +81-3-3843-3141 FAX +81-3-3843-3144 1-26-20 Kasukabehigashi, Kasukabe-shi, Saitama 344-0062, Japan TEL +81-48-760-3881 FAX +81-48-760-3883





B573 Surface attached adjuster felf type PAT.P

Adjuster cap







B573-25-BL

Adjuster seat





- Hard to scratch contact area because of felt
- Imposition makes unnecessary to process into wooden
- Size is ϕ 25. It's possible to install thin and small surface such table legs
- Installation is easy. Even if it needs an adjuster, it's possible to install with only a driver.
- Superial material being durable for low temperature, so it's not broken easily
- Easy to turn because it has knurling
- Adjustment width is 5mm
- Recommended screw/round screw for wood ϕ 3.5, Pan head screw ϕ 3.5
- Indoor use
- Finishing/ White · Black
- Material/POM
- Applicable floor material/P tile, flooring
- *Load capacity is static load Caution: It might happen to be broken if it gets shock within its load capacity
- Please refrain to use things such as a chair or sofa expecting shock When you use, use in a tightened state a cap

Save time to work!! **B573 Usual item (current)** Necessary to process of wood Fix with screw directly

Specification dimension Unit: mm Product number Specification Load capacity (kg) Quantity B573-25-WH 150 B573-25-BL 240 WH/BL(seat) B573-25-PL B573-25-CP WH/BL(cap)

If the movement of adjustment is hard, tighten a screw of adjustment seat so that it does not wobble.

Caution: Using an impact driver, if you screw too tightened, movement of adjustment might become hard.

Installation image




B573-25-WH





B573-25-BL

Installation image (Only adjust seat)









Recommended screw/round screw for wood ϕ 3.5, pan head screw ϕ 3.5

**Real total height becomes 17mm with felt



Head office

3-4-1 Motoasakusa, Taito-ku, Tokyo 111-0041, Japan TEL +81-3-3843-3141 FAX +81-3-3843-3144

Kasukabe branch 1-26-20 Kasukabehigashi, Kasukabe-shi, Saitama 344-0062, Japan TEL +81-48-760-3881 FAX +81-48-760-3883



